

AUTOLOADER LTO 1, 2, 3 & 4 20 CARTRIDGE DATA ERASER, CLEANER & CERTIFIER The **WILTEC** Model 510B

**NO ATTENDANT REQUIRED..
AUTOMATIC OPERATION**



WILTEC Model 510B LTO1/2/3/4 20 Cartridge High Speed Automatic ERASER, CERTIFIER, CLEANER and RETENSIONER

The WILTEC Model 510B Autoloading LTO Cartridge ERASER unit can be tabletop or rackmounted. Dual slide-out cartridge magazines illustrated at the right make loading fast and easy. High Speed Option doubles speed to 30 cartridges/hour throughput.

SPECIFICATIONS

Functional Data

Media LTO Cartridge Accomodated: MOD510A-2 LTO1 & LTO2
LTO Cartridge Accomodated: MOD510A-3 LTO2 & LTO3
LTO Cartridge Accomodated: MOD510A-4 LTO3 & LTO4

Number of Cartridges/Load: 20

Number of Tape Drives: 1 (2 for High Speed Option)

Time for System to Degauss, per Cartridge: 4 mins.

WILTEC'S Precision Erase Head ERASES 4 Data Bands in One BOT to EOM Pass, Preserves Servo Bands.

Recertified "Like New" and new components employed

Reliability

Mean Exchanges Between

Failures (MEBF) 500,000

Mean Time To Repair (MTTR) 1 hr. FRU Exch, depot

- **THRUPUT: 15/30 CARTRIDGES/HOUR**
- **ERASE TIME: 4 MINUTES/CARTRIDGE, HIGH SPEED OPTION ERASES 30 CARTRIDGES/HOUR**
- **UNATTENDED OPERATION AFTER LOADING**
- **FAST MAGAZINE LOAD**
- **PRECISION ERASE HEAD PRESERVES SERVO BANDS... GUARANTEED**
- **PASS (GREEN) and FAIL (RED) CERTIFIER INDICATORS**
- **SYSTEM READY (BLUE) and DATA ERASING (AMBER) SYSTEM STATUS INDICATORS**
- **Meets/Exceeds DoD 5220.22-M Tape Media Degauss/Erase Specifications**



WILTEC Model 510B LTO1/2/3/4 Dual Magazines/Tape Handlers make for fast and easy new load ERASE resumption.

Physical Dimensions

Width (footprint)	19 in.
Height	8.5 in.
Depth	27 in.
Weight	90 lbs

Power Requirements

Input Voltage	90-264 VAC 1 Phase
Frequency	47-63 Hz
Max Power Consumption	500 V A

Note: Prices, availability and specifications subject to change without notice.

[Click here to return to the first page](#)

WILTEC

WILTEC Inc.
116 S. Kerr Business Park,
Suite D
Wilmington, NC 28405

TEL: 910-763-8400
FAX: 910-763-0942
www.wiltec.com
info@wiltec.com